



Kołnierz z szyjką do przyspawania typ 11 wg EN 1092-1: 2013

Ciśnienie nominalne PN 160

Śred. nom. DN	Kołnierz											Śruby			
	A	D	K	L	H ₂	C ₂	N ₁	H ₃	R	s	d ₁	f ₁	masa kg	n	gwint
10	17,2	100	70	14	45	20	32	6	4	2	40	2	1,10	4	M12
15	21,3	105	75	14	45	20	34	6	4	2	45	2	1,20	4	M12
25	33,7	140	100	18	58	24	52	8	4	2,9	68	2	2,64	4	M16
40	48,3	170	125	22	64	28	70	10	6	3,6	88	3	4,42	4	M20
50	60,3	195	145	26	75	30	90	10	6	4	102	3	6,38	4	M24
65	76,1	220	170	26	82	34	108	12	6	5	122	3	8,75	8	M24
80	88,9	230	180	26	86	36	120	12	8	6,3	138	3	10,30	8	M24
100	114,3	265	210	30	100	40	150	12	8	8	162	3	15,30	8	M27
125	139,7	315	250	33	115	44	180	14	8	10	188	3	24,40	8	M30
150	168,3	355	290	33	128	50	210	14	10	12,5	218	3	34,40	12	M30
200	219,1	430	360	36	140	60	278	16	10	16	285	3	60,70	12	M33
250	273,0	515	430	42	155	68	340	18	12	20	345	3	97,60	12	M36
300	323,9	585	500	42	175	78	400	18	12	22,2	410	4	140,00	16	M39