



Kołnierz z szyjką do przyspawania typ 11 wg EN 1092-1: 2013

Ciśnienie nominalne PN 250

Śred. nom. DN	Kołnierz											Śruby			
	A	D	K	L	H ₂	C ₂	N ₁	H ₃	R	s	d ₁	f ₁	masa kg	n	gwint
10	17,2	125	85	18	58	24	44	6	4	2,6	40	2	2,14	4	M16
15	21,3	130	90	18	60	26	48	6	4	2,6	45	2	2,51	4	M16
25	33,7	150	105	22	65	28	60	8	4	3,6	68	2	3,58	4	M20
40	48,3	185	135	26	80	34	84	10	6	5	88	3	6,72	4	M24
50	60,3	200	150	26	85	38	95	10	6	6,3	102	3	8,22	8	M24
65	76,1	230	180	26	95	42	124	12	6	8	122	3	12,80	8	M24
80	101,6	255	200	30	102	46	136	12	8	11	138	3	16,50	8	M27
100	127,0	300	235	33	120	54	164	14	8	14,2	162	3	27,20	8	M30
125	152,4	340	275	33	140	60	200	16	8	16	188	3	39,00	12	M30
150	177,8	390	320	36	160	68	240	18	10	17,5	218	3	59,60	12	M33
200	244,5	485	400	42	190	82	305	25	10	25	285	3	110,00	12	M39
250	298,5	585	490	48	215	100	385	30	12	32	345	3	190,00	16	M45