



Kołnierz z szyjką do przyspawania typ 11 wg EN 1092-1: 2013

Ciśnienie nominalne PN 320

Śred. nom.	Kołnierz											Śruby				
	DN	A	D	K	L	H ₂	C ₂	N ₁	H ₃	R	s	d ₁	f ₁	masa kg	n	gwint
10	17,2	125	85	18	58	24	44	6	4	4	2,6	40	2	2,14	4	M16
15	21,3	130	90	18	60	26	48	8	4	4	3,2	45	2	2,53	4	M16
25	33,7	160	115	22	78	34	68	8	4	4	5	68	2	5,18	4	M20
40	48,3	195	145	26	88	38	92	10	6	6,3	88	88	3	8,65	4	M24
50	63,5	210	160	26	100	42	106	10	6	8	102	102	3	10,70	8	M24
65	88,9	255	200	30	120	51	138	12	6	11	122	122	3	19,50	8	M27
80	101,6	275	220	30	130	55	156	14	8	12,5	138	138	3	25,20	8	M27
100	133,0	335	265	36	145	65	186	16	8	16	162	162	3	42,50	8	M33
125	168,3	380	310	36	175	75	230	20	8	20	188	188	3	63,60	12	M33
150	193,7	425	350	39	195	84	265	25	10	25	218	218	3	91,50	12	M36
200	244,5	525	440	42	235	103	345	30	10	30	285	285	3	172,00	16	M39
250	323,9	640	540	52	300	125	428	40	12	40	345	345	3	312,00	16	M48