



Kołnierz tulejowy nasuwany do przyspawania - typ 12 wg EN 1092-1: 2013

Ciśnienie nominalne PN 63

Śred. nom. DN	Rura		Kołnierz										Śruby	
	A	B ₁	D	K	L	H ₁	C ₂	N ₂	R	d ₁	f ₁	masa kg	n	gwint
10	17,2	18	100	70	14	28	20	40	4	40	2	1,07	4	M12
15	21,3	22,0	105	75	14	28	20	43	4	45	2	1,17	4	M12
20	26,9	27,5	130	90	18	30	22	52	4	58	2	1,96	4	M16
25	33,7	34,5	140	100	18	32	24	60	4	68	2	2,49	4	M16
32	42,4	43,5	155	110	22	32	24	68	6	78	2	2,95	4	M20
40	48,3	49,5	170	125	22	34	26	80	6	88	3	3,80	4	M20
50	60,3	61,5	180	135	22	36	26	90	6	102	3	4,20	4	M20
65	76,1	77,5	205	160	22	40	26	112	6	122	3	5,30	8	M20
80	88,9	90,5	215	170	22	44	28	125	8	138	3	6,25	8	M20
100	114,3	116	250	200	26	52	30	152	8	162	3	8,81	8	M24
125	139,7	141,5	295	240	30	56	34	185	8	188	3	13,60	8	M27
150	168,3	170,5	345	280	33	60	36	215	10	218	3	19,50	8	M30