



Kołnierz zaślepiający - typ 05 wg EN 1092-1:2013

Ciśnienie nominalne PN 6

| Śred. nom. DN | Kołnierz | | | | | | Śruby | | |
|---------------|----------|------|----|----------------|----------------|----------------|---------|----|-------|
| | D | K | L | C ₄ | d ₁ | f ₁ | masa kg | n | gwint |
| 10 | 75 | 50 | 11 | 12 | 35 | 2 | 0,50 | 4 | M10 |
| 15 | 80 | 55 | 11 | 12 | 40 | 2 | 0,50 | 4 | M10 |
| 20 | 90 | 65 | 11 | 14 | 50 | 2 | 0,50 | 4 | M10 |
| 25 | 100 | 75 | 11 | 14 | 60 | 2 | 1,00 | 4 | M10 |
| 32 | 120 | 90 | 14 | 14 | 70 | 2 | 1,00 | 4 | M12 |
| 40 | 130 | 100 | 14 | 14 | 80 | 3 | 1,50 | 4 | M12 |
| 50 | 140 | 110 | 14 | 14 | 90 | 3 | 1,50 | 4 | M12 |
| 65 | 160 | 130 | 14 | 14 | 110 | 3 | 2,00 | 4 | M12 |
| 80 | 190 | 150 | 18 | 16 | 128 | 3 | 3,50 | 4 | M16 |
| 100 | 210 | 170 | 18 | 16 | 148 | 3 | 4,00 | 4 | M16 |
| 125 | 240 | 200 | 18 | 18 | 178 | 3 | 6,00 | 8 | M16 |
| 150 | 265 | 225 | 18 | 18 | 202 | 3 | 7,50 | 8 | M16 |
| 200 | 320 | 280 | 18 | 20 | 258 | 3 | 12,50 | 8 | M16 |
| 250 | 375 | 335 | 18 | 22 | 312 | 4 | 18,50 | 12 | M16 |
| 300 | 440 | 395 | 22 | 22 | 365 | 4 | 25,50 | 12 | M20 |
| 350 | 490 | 445 | 22 | 22 | 415 | 4 | 32,00 | 12 | M20 |
| 400 | 540 | 495 | 22 | 22 | 465 | 4 | 38,50 | 16 | M20 |
| 450 | 595 | 550 | 22 | 24 | 520 | 4 | 51,00 | 16 | M20 |
| 500 | 645 | 600 | 22 | 24 | 570 | 4 | 60,03 | 20 | M20 |
| 600 | 755 | 705 | 26 | 30 | 670 | 5 | 103,00 | 20 | M24 |
| 700 | 860 | 810 | 26 | 40 | 775 | 5 | 178,50 | 24 | M24 |
| 800 | 975 | 920 | 30 | 44 | 880 | 5 | 252,00 | 24 | M27 |
| 900 | 1075 | 1020 | 30 | 48 | 980 | 5 | 335,50 | 24 | M27 |
| 1000 | 1175 | 1120 | 30 | 52 | 1080 | 5 | 434,50 | 28 | M27 |
| 1200 | 1405 | 1340 | 33 | 60 | 1295 | 5 | 717,50 | 32 | M30 |
| 1400 | 1630 | 1560 | 36 | 68 | 1510 | 5 | 1094,00 | 36 | M33 |
| 1600 | 1830 | 1760 | 36 | 76 | 1710 | 5 | 1545,00 | 40 | M33 |
| 1800 | 2045 | 1970 | 39 | 84 | 1920 | 5 | 2131,00 | 44 | M36 |
| 2000 | 2265 | 2180 | 42 | 92 | 2125 | 5 | 2862,00 | 48 | M39 |