



Kołnierz płaski do przyspawania – typ 01 wg EN 1092-1: 2013

Ciśnienie nominalne PN 2,5

Śred. nom. DN	Rura		Kołnierz						Śruby		
	A	B ₁	D	K	d ₁	f ₁	C ₁	L	masa kg	n	gwint
10	13,5*	14	75	50	35	2	12	11	0,36	4	M10
	17,2	18							0,36		
15	20,0*	20,5	80	55	40	2	12	11	0,41	4	M10
	21,3	22							0,40		
20	25,0*	26	90	65	50	2	14	11	0,60	4	M10
	26,9	27,5							0,59		
25	30,0*	32	100	75	60	2	14	11	0,74	4	M10
	33,7	34,5							0,72		
32	38,0*	39	120	90	70	2	16	14	1,20	4	M12
	42,4	43,5							1,16		
40	44,5*	45,5	130	100	80	3	16	14	1,40	4	M12
	48,3	49,5							1,35		
50	57,0*	58	140	110	90	3	16	14	1,50	4	M12
	60,3	61,5							1,48		
65	76,1	77,5	160	130	110	3	16	14	1,86	4	M12
80	88,9	90,5	190	150	128	3	18	18	2,95	4	M16
100	108,0*	109	210	170	148	3	18	18	3,30	4	M16
	114,3	116							3,26		
125	133,0*	135	240	200	178	3	20	18	4,40	8	M16
	139,7	141,5							4,31		
150	159,0*	161	265	225	202	3	20	18	4,80	8	M16
	168,3	170,5							4,76		
200	219,1	221,5	320	280	258	3	22	18	6,88	8	M16
250	273,0	276,5	375	335	312	3	24	18	8,92	12	M16
300	323,9	327,5	440	395	365	4	24	22	11,90	12	M20
350	355,6	359,5	490	445	415	4	26	22	16,80	12	M20
400	406,4	411	540	495	465	4	28	22	19,80	16	M20
450	457,0	462	595	550	520	4	30	22	24,60	16	M20
500	508,0	513,5	645	600	570	4	30	22	26,40	20	M20
600	610,0	616,5	755	705	670	5	32	26	34,80	20	M24
700	711,0		860	810	775	5	40	26	-	24	M24
800	813,0		975	920	880	5	44	30	-	24	M27
900	914,0		1075	1020	980	5	48	30	-	24	M27
1000	1016,0		1175	1120	1080	5	52	30	-	28	M27
1200	1219,0		1375	1320	1280	5	60	30	-	32	M27
1400	1422,0		1575	1520	1480	5		30	-	36	M27
1600	1626,0		1790	1730	1690	5		30	-	40	M27
1800	1829,0		1990	1930	1890	5		30	-	44	M27
2000	2032,0		2190	2130	2090	5		30	-	48	M27

*) średnice rur nie przewidziane normą EN 1092-1:2013 - mogą być wykonane na specjalne zamówienie klienta.