



Kołnierz z szyjką do przyspawania typ 11 wg EN 1092-1: 2013

Ciśnienie nominalne PN 400

Śred. nom. DN	Kołnierz											Śruby			
	A	D	K	L	H ₂	C ₂	N ₁	H ₃	R	s	d ₁	f ₁	masa kg	n	gwint
10	17,2	125	85	18	65	28	48	8	4	3,6	40	2	2,55	4	M16
15	26,9	145	100	22	68	30	56	8	4	5	45	2	3,62	4	M20
25	42,4	180	130	26	90	38	82	10	4	7,1	68	2	7,45	4	M24
40	60,3	220	165	30	110	48	106	12	6	10	88	3	14,10	4	M27
50	76,1	235	180	30	120	52	120	15	6	12,5	102	3	16,70	8	M27
65	101,6	290	225	33	135	64	158	18	6	16	122	3	31,60	8	M30
80	114,3	305	240	33	150	68	174	20	8	17,5	138	3	38,40	8	M30
100	139,7	370	295	39	175	80	216	25	8	22,2	162	3	67,30	8	M36
125	193,7	415	340	39	200	92	258	30	8	30	188	3	94,50	12	M36
150	219,1	475	390	42	225	105	302	35	10	35	218	3	145,00	12	M39
200	273,0	585	490	48	280	130	388	40	10	40	285	3	270,00	16	M45