



### Kołnierz tulejowy nasuwany do przyspawania - typ 12 wg EN 1092-1: 2013

Ciśnienie nominalne PN 100

Śred. nom. DN	Rura		Kołnierz									Śruby		
	A	B <sub>1</sub>	D	K	L	H <sub>1</sub>	C <sub>2</sub>	N <sub>2</sub>	R	d <sub>1</sub>	f <sub>1</sub>	masa kg	n	gwint
10	17,2	18	100	70	14	28	20	40	4	40	2	1,07	4	M12
15	21,3	22,0	105	75	14	28	20	43	4	45	2	1,17	4	M12
20	26,9	27,5	130	90	18	30	22	52	4	58	2	1,96	4	M16
25	33,7	34,5	140	100	18	32	24	60	4	68	2	2,49	4	M16
32	42,4	43,5	155	110	22	32	24	68	6	78	2	2,95	4	M20
40	48,3	49,5	170	125	22	34	26	80	6	88	3	3,80	4	M20
50	60,3	61,5	195	145	26	36	28	95	6	102	3	5,28	4	M24
65	76,1	77,5	220	170	26	40	30	118	6	122	3	6,84	8	M24
80	88,9	90,5	230	180	26	44	32	130	8	138	3	7,94	8	M24
100	114,3	116	265	210	30	52	36	158	8	162	3	11,50	8	M27
125	139,7	141,5	315	250	33	56	40	188	8	188	3	17,90	8	M30
150	168,3	170,5	355	290	33	60	44	225	10	218	3	23,80	12	M30