



Kolana wg ANSI B16.9 typ SR

Średnica nominalna	Średnica zewn. dz	Kąt	Grubości ścianek											
			R	b	SCH 20		SCH 30		STD		SCH 40		SCH 60	
					s	masa	s	masa	s	masa	s	masa	s	masa
Cale	mm		mm	mm	mm	kg	mm	kg	mm	kg	mm	kg	mm	kg
3"	88,9	90°	76	121	-	-	-	-	5,49	1,38	5,49	1,38	-	-
		45°	-	-	-	-	-	-	-	0,69	-	0,69	-	-
3 1/2"	101,6	90°	89	140	-	-	-	-	5,74	1,93	5,74	1,93	-	-
		45°	-	-	-	-	-	-	-	0,96	-	0,96	-	-
4"	114,3	90°	102	159	-	-	-	-	6,02	2,62	6,02	2,62	-	-
		45°	-	-	-	-	-	-	-	1,31	-	1,31	-	-
5"	141,3	90°	127	197	-	-	-	-	6,55	4,42	6,55	4,42	-	-
		45°	-	-	-	-	-	-	-	2,21	-	2,21	-	-
6"	168,3	90°	152	237	-	-	-	-	7,11	6,90	7,11	6,90	-	-
		45°	-	-	-	-	-	-	-	3,45	-	3,45	-	-
8"	219,1	90°	203	313	6,35	11,16	7,04	12,34	8,18	13,80	8,18	13,80	10,31	17,80
		45°	-	-	-	5,58	-	6,17	-	6,90	-	6,90	-	8,90
10"	273,0	90°	254	391	6,35	17,48	7,80	31,36	9,27	24,50	9,27	24,50	12,70	32,90
		45°	-	-	-	8,74	-	15,60	-	12,25	-	12,25	-	16,45
12"	323,8	90°	305	467	6,35	24,97	8,38	32,75	9,53	36,10	10,31	40,05	14,20	54,90
		45°	-	-	-	12,50	-	16,40	-	18,05	-	20,00	-	27,45
14"	355,6	90°	356	533	7,92	39,80	9,53	47,6	9,53	46,30	11,13	55,45	15,01	74,40
		45°	-	-	-	19,90	-	23,80	-	23,15	-	25,00	-	37,00

Kolana wg ANSI B16.9 typ SR

Średnica nominalna	Średnica zewn. dz	Kąt	Grubości ścianek											
			R	b	XS		SCH 80		SCH 100		SCH 120		SCH 140	
					s	masa	s	masa	s	masa	s	masa	s	masa
Cale	mm		mm	mm	mm	kg	mm	kg	mm	kg	mm	kg	mm	kg
3"	88,9	90°	76	121	7,62	1,83	7,62	1,83	-	-	-	-	-	-
		45°	-	-	-	0,91	-	0,91	-	-	-	-	-	-
3 1/2"	101,6	90°	89	140	8,08	2,61	8,08	2,61	-	-	-	-	-	-
		45°	-	-	-	1,30	-	1,30	-	-	-	-	-	-
4"	114,3	90°	102	159	8,56	3,58	8,56	3,58	-	-	11,13	4,80	-	-
		45°	-	-	-	1,78	-	1,78	-	-	2,40	-	-	-
5"	141,3	90°	127	197	9,53	6,21	9,53	6,21	-	-	12,70	8,50	-	-
		45°	-	-	-	3,10	-	3,10	-	-	4,20	-	-	-
6"	168,3	90°	152	237	10,97	10,30	10,97	10,30	-	-	14,27	13,60	-	-
		45°	-	-	-	1,15	-	5,15	-	-	6,80	-	-	-
8"	219,1	90°	203	313	12,70	20,70	12,70	20,70	15,09	25,50	18,26	30,30	20,62	33,80
		45°	-	-	-	10,35	-	10,35	-	12,70	-	15,10	-	16,90
10"	273	90°	254	391	12,70	32,90	15,09	40,20	18,26	47,90	21,44	55,70	25,40	60,90
		45°	-	-	-	16,40	-	20,10	-	23,80	-	27,80	-	30,45
12"	323,8	90°	305	467	12,70	47,20	17,48	66,20	21,44	80,20	25,40	93,90	28,58	104,60
		45°	-	-	-	23,60	-	33,10	-	40,10	-	46,90	-	52,30
14"	355,6	90°	356	533	12,70	61,20	19,05	92,70	23,83	114,2	27,79	131,70	31,75	148,60
		45°	-	-	-	30,60	-	46,30	-	57,00	-	65,80	-	74,30